



13	Name Plate	Stainless Steel	銘板	SUS304	1
12	Gasket	PTFE	ガスケット	PTFE	1
11	Gasket	PTFE	ガスケット	PTFE	1
10	Cap	Stainless Steel	キャップ	SUS303	1
9	Lock Nut	Stainless Steel	ロックナット	SUS303	1
8	Adjusting Screw	Stainless Steel	調整ねじ	SUS303	1
7	Top Spring Plate	Stainless Steel	上部ばね受	SUS304 or SUS303	1
6	Bottom Spring Plate	Stainless Steel	下部ばね受	SUS304 or SUS303	1
5	Spring	Stainless Steel	ばね	SUS304	1
4	Spindle	Stainless Steel	弁軸	SUS303	1
3	Valve	Stainless Steel	弁体	SUS304	1
2	Valve Seat	Stainless Steel	弁座	SUS304	1
1	Spring Case	Cast Stainless Steel	ばね箱	SCS14A or SCS13	1
No.	Name of Parts	Material	部品名	材質	Q. TY

(mm)					
Size	d	L	H <sub>1</sub>	H	Weight (kg)
15A	Rc 1/2	34	41	129	0.7
20A	Rc 3/4	38	45	132	0.9
25A	Rc 1	43	51.5	148	1.2
32A	Rc 1 1/4	50	63.5	184	2.2
40A	Rc 1 1/2	60	68.5	210	3.2
50A	Rc 2	75	80	250	5.6

Specification	
Fluid	
Set Press.	MPa
Temp.	℃
Flow Rate	

TYPE AL-250 RELIEF VALVE

リリーフ弁

Approval	H. Iwamoto
Check	H. Ishihara
Drawing	H. Kamada
Drawing No.	Y-1014-3601-1A
Date	22 NOV. 2016

**Yoshitake**  
INC.