



6	Plug	Stainless Steel or Cast Stainless Steel	プラグ	SUSorSCS	1
5	Bolt	Stainless Steel	ボルト	SUS	1Set
4	Gasket	PTFE	ガスケット	PTFE	1
3	Screen	Stainless Steel	スクリーン	SUS304	1
2	Cover	Cast Stainless Steel	ふた	SCS13	1
1	Body	Cast Stainless Steel	本体	SCS13	1
No.	Name of Parts	Material	部品名	材質	Q. TY

Size	L	H ₁	Screen		d	Flange JIS 10K FF				Plug ◎	Weight (kg)
			d _s	l _s		D	t	C	n-h		
65A	270	162	73	125	65	175	18	140	4-19	R 1/2	13.2
80A	290	185	88	130	80	185	18	150	8-19	R 1/2	17.2
100A	350	222	108	180	100	210	18	175	8-19	R 1/2	26.0

Specification	
Fluid	
Press.	MPa
Temp.	℃
Flow Rate	
Inside Screen	Mesh
Outside Screen	Ø - ㄱ/cm ²

TYPE SY-8 STRAINER
ストレーナ

Approval	H. Iwamoto
Check	K. Takenaka
Drawing	S. Harita
Drawing No.	Y-136-3505-7A
Date	13 JAN. 2017

