



8	Name Plate	Aluminium	銘板	A1050	1
5	Gasket	Non-Asbestos	ガスケット	Non-Asbestos	1
4	Plug	Carbon Steel or Malleable Cast Iron	プラグ	S15C or FCMB	1
3	Screen	Stainless Steel	スクリーン	SUS304	1
2	Cap	Ductile Cast Iron	キャップ	FCD450	1
1	Body	Ductile Cast Iron	本体	FCD450	1
No.	Name of Parts	Material	部品名	材質	Q. TY

④ SIZE: 40A~50A

Size	L	H <sub>1</sub>	d	Screen		Flange JIS 20K FF				④ Plug	Weight (kg)
				ds	ls	D	C	t	n-h		
15A	130	61	15	22	40	95	70	16	4-15	—	1.9
20A	140	75	20	27	56	100	75	16	4-15	—	2.5
25A	160	88	25	34	66	125	90	18	4-19	—	4.0
32A	175	104	35	43	76	135	100	20	4-19	—	5.2
40A	190	115	40	50	85	140	105	20	4-19	R 1/2	6.7
50A	233	140	50	61	107	155	120	20	8-19	R 1/2	10.2

\*フランジ厚みは規格より厚くなっております。

\*Thickness of Flange thicker than standard type

Specification	
Fluid	
Press.	MPa
Temp.	℃
Flow Rate	
Inside Screen	Mesh
Outside Screen	Ø - ㄎ/cm <sup>2</sup>

TYPE SY-40H STRAINER  
ストレーナ

Approval	H. Iwamoto
Check	Y. Aoyama
Drawing	H. Okumura
Drawing No.	Y-1080-2109-3A
Date	26 AUG. 2013

