



12	Joint	Brass	継手	C3604	1
11	Elbow	Brass	エルボー	C3771	1
10	Pipe D	Copper	導管D	C1220	1
9	Pipe C	Copper	導管C	C1220	1
8	Pipe B	Copper	導管B	C1220	1
7	Elbow	Brass	エルボー	C3771	1
6	Tee	Brass	ティー	C3771	1
5	Nipple	Carbon Steel	ニップル 1/4	S25C	1
4	Long Nipple	Carbon Steel	ロングニップル 1/4	STPG	1
3	Pilot Valve DP-11A (With Terminal Box)	Brass	子弁 DP-11A (端子箱付)	C3771	1
2	Pilot Valve OB-2000P	Bronze	子弁 OB-2000P	CAC406	1
1	Main Valve GPM-2000	Ductile Cast Iron	親弁 GPM-2000	FCD450	1
No.	Name of Parts	Material	部品名	材質	Q. TY

(mm)

Size	L	H <sub>1</sub>	H	A	E	F	G	Flange JIS 10K FF					Weight (kg)
								d	D	C	t	n-h	
15A	142	170	244	200	155	180	232	15	95	70	12	4-15	15.6
20A	142	170	244	200	155	180	232	20	100	75	14	4-15	16.1
25A	152	175	251	226	156	185	237	25	125	90	14	4-19	21.0
32A	172	192	282	226	165	193	245	32	135	100	16	4-19	23.9
40A	192	192	282	226	165	193	245	40	140	105	16	4-19	24.4
50A	218	216	319	276	170	200	252	50	155	120	16	4-19	35.3
65A	278	251	373	352	185	217	269	65	175	140	18	4-19	62.9
80A	294	264	399	352	190	228	280	80	185	150	18	8-19	67.8
100A	330	321	488	401	215	245	297	100	210	175	18	8-19	106.1

Specification	
Fluid	
Inlet Press.	MPa
Set Temp.	℃
Temp. Regulation Range	℃
Voltage	
Operation	
Flow Rate	

TYPE CP-2006 CONBINATION VALVE  
コンビネーションバルブ

Approval	H. Iwamoto
Check	M. Yoshida
Drawing	Y. Aoyama
Drawing No.	Y-789-2205-1A
Date	20 DEC. 2012

